






CAD FILE:



SCHEMATIC

- 1、开关动作力: $100 \pm 30\text{gf} \cdot \text{cm}$
- 2、回返力: $30\text{gf} \cdot \text{cm}$ Min
- 3、额定值: DC30V 0.1A
- 4、接触电阻: $200\text{m}\Omega$ Max
- 5、绝缘电阻: $\geq 100\text{M}\Omega$ (MinDC250V)
- 6、耐压: 250V AC (50HZ或60HZ)/1min
- 7、机械寿命: 50000 Min



P.C.B LAYOUT
BOTTOM VIEW

注“*”表示关键尺寸(8个)

8					TOLERANCE							
7					UNLESS SPECIFIED		B	2020-05-23	原数1.2			
6	TERMINAL	BRASS	1	Ag PLATED	WITHIN 1.5mm : ±0.1mm		A	2019-11-26	初 版			
5	CASE	PA66	1	BLACK	OVER 1.5mm : ±0.2mm		ISSUE	DATE	DESCRIPTIONS OF REVISION		APPD.	
4	SPRING	SUS	1	NATURAL	TITLE : PUSH SWITCH				UNIT : mm	DRWG NO.:		
3	CONTACT	BRONAE	1	Ag PLATED	MODEL: TC-0028				SCALE: 5:1	DWN.		2020-05-23
2	BUTTON	PA66	1	YELLOW	DONGGUAN AUGO ELECTRONICS CO.,LTD.				CHK'D		2020-05-23	
1	COVER	PA66	1	BLACK					APPD.		2020-05-23	
NO.	PARTS	MATERIALS	QTY	FINISH								