

Rohs

REV.	DESCRIPTION	DRAW.	DATE.

PART NO.	DIM A	DIM B	DIM C
AUGO-BC-15-3PD380	9.0	5.0	2.5
AUGO-BC-15-4PD380	11.5	7.5	5.0
AUGO-BC-15-5PD380	14.0	10.0	7.5
AUGO-BC-15-6PD380	16.5	12.5	10.0

Material :

Insulator : LCP(UL94V-0)

Contact : Phosphor Bronze

Contact Plated : Gold over Nickel or Tin

Specification :

Current Rating : 2A

Voltage Rating : 12V

Contact Resistance : 30m Ω

Insulation Resistance : 500M Ω

Dielectric Voltage : 500V

Operating Temperature : -40°~85°

Electrical Life : 3000cycles

RECOMMENDED PCB LAYOUT
TOL: (±0.05)

AUGO

AUGO ELECTRONICS CO.,LTD.

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

REV:	01	UNLESS OTHERWISE SPECIFIED,TOLERANCE:	TITLE:	2.5 PITCH BATTERY CONNECTOR	DESIGN	G.C.CHEN	DATE	
SIZE:	A4				DRAWING	Y.C.ZHANG	DATE	
SCALE: 1:1	UNIT: mm	X.	PART NO:	AUGO-BC-15H380	CHECK	D.J.WANG	DATE	
SHEET: 1/1		X.x			SCALE	1:1	PAGE	1 OF 1
		X.xx						
		ANGULAR						