



NOTES:

1. MATERIAL:

- 1.1 HOUSING:THERMOPLASTIC FLAMMABILITY RATING UL94-0
- 1.2 CONTACT: COPPERY ALLOY T=0.15MM
- 1.3 SHELL: COPPERY ALLOY T=0.25MM

2. FINISH:

- 2.1 CONTACT:
 - 3U"MIN,PLATED ON CONTACT AREA
 - G/F PLATING ON SOLDER TAIL AREA
 - 50~80U" NICKEL UNDERPLATING OVERALL
- 2.2 SHELL:
 - 80~120U" MATTER TIN PLAING ALL
 - 50~80U" NICKEL UNDERPLATING OVERALL

3. SPECIFICATION:

- 3.3 CURRENT RATING:0.5A(2.3.4CONTACT)/1.8A (1.5CONTACT)MAX.
- 3.2 VOLTAGE:30 VAC
- 3.3 TEMPERATURE RANGE:-30°C~85°C
- 3.4 CONTACT RESISTANCE:30 MILLIONHM MAX.
- 3.5 DIELECTRIC WITHSTANDING VOLTAGE;250VAC R.M.S
- 3.6 INSULATION RESISTNACE:100 MEGOHMS MIN

DONGGUAN AUGO ELECTRONICS CO.,LTD.

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		CONNECTOR		DRAWING	Y,C,ZHANG	DWG.No.	
PART NO.		MICRO USB 5PIN SMT 5.5MM		CHECK	G.C.Chen	REV.	A1
UNIT : mm	TOLERANCE OTHERWISE	UP TO 5	±0.2	ANGLE	APPROVAL	DATE	
		ABOVE 5~30	±0.3				
		ABOVE 30	±0.5	0°±3°	SCALE	PAGE	1 OF 1
		ANGLE	±3°		2:1		