



材料:
 A底座/基座: LCP(黑色)
 B嵌件: C5191R(整体镀银与银白色)
 C桃心: 高温尼龙(白色)
 D簧片: QBe2(接触单面镀银与接触面银白色)
 E盖板: C5191R(整体镀银与银白色)
 F弹条: SUS301(整体清洗与银白色)

主要技术规格:

1. 额定值: 50mA MAX
2. 接触电阻: $\leq 70m\Omega$
3. 操作力: $180gf \pm 50gf$
4. 行程: $1.5 \pm 0.2mm$
5. 绝缘电阻: $\geq 100M\Omega$
6. 耐压强度: AC250V 50HZ/ 1Min.
7. 寿命: 1万Cycles Min
8. 额定电压: DC 12V

DONGGUAN AUGO ELECTRONIC CO., LTD.

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME		SWITCH		DRAWING		Y,C,ZHANG	DWG.No.	SBICL
PART NO.		MSK-1292S		CHECK		G.C.Chen	REV.	A1
UNIT :	TOLERANCE OTHERWISE	UP TO 5	± 0.2	ANGLE	APPROVAL	DATE	14-03-2013	1 OF 1
		ABOVE 5 ~ 30	± 0.3					
mm		ABOVE 30	± 0.5	$0^\circ \pm 5'$	SCALE	PAGE		