



材料:
 A底座/基座: LCP(黑色)
 B嵌件: C5191R (整体镀银与银白色)
 C手柄: 进口增强尼龙
 D簧片: QBe2 (接触单面镀银与接触面银白色)
 E盖板: C5191R (整体镀银)
 F弹条: SUS301 (整体清洗与银白色)

- 主要技术规格:
1. 额定值: 50mA MAX
 2. 接触电阻: $\leq 70m\Omega$
 3. 操作力: $150gf \pm 50gf$
 4. 行程: $1.2 \pm 0.2mm$
 5. 绝缘电阻: $\geq 100M\Omega$
 6. 耐压强度: AC250V 50HZ/ 1Min.
 7. 寿命: 1万Cycles Min
 8. 额定电压: DC 12V

DONGGUAN AUGO ELECTRONIC CO., LTD.

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME		SWITCH		DRAWING	Y,C,ZHANG	DWG.No.	SBICL
PART NO.		MSK-1293S		CHECK	G.C.Chen	REV.	A1
UNIT :	TOLERANCE OTHERWISE	UP TO 5	± 0.2	APPROVAL	SCALE	DATE	14-03-2013
		ABOVE 5~30	± 0.3			PAGE	1 OF 1
mm		ABOVE 30	± 0.5		2:1		
		ANGLE	$\pm 3'$				