



材料:

- A 基座: 进口增强尼龙 (黑色)
- B 嵌件: 磷铜 (整体镀银与银白色)
- C 手柄: 进口增强尼龙 (黑色)
- D 簧片: 铍青铜 (镀银与银白色)
- E 盖板: 不锈钢 (清洗)

主要技术规格:

1. 额定值: 50mA MAX
2. 接触电阻: $\leq 70m\Omega$
3. 操作力: $180gf \pm 50gf$
4. 行程: $2 \pm 0.2mm$
5. 绝缘电阻: $\geq 100M\Omega$
6. 耐压强度: AC250V 50HZ/ 1Min.
7. 寿命: 1万Cycles Min
8. 额定电压: DC 12V

DONGGUAN AUGO ELECTRONIC CO., LTD.

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME		SWITCH		DRAWING	Y,C,ZHANG	DWG.No.	SBICL
PART NO.		MSK-12D70S		CHECK	G.C.Chen	REV.	A1
UNIT :	TOLERANCE OTHERWISE	UP TO 5	± 0.2	ANGLE	APPROVAL	DATE	14-03-2013
		ABOVE 5 ~ 30	± 0.3				
mm		ABOVE 30	± 0.5	0 ± 3	SCALE	PAGE	1 OF 1
		ANGLE	± 3				