






Rohs

REV.	DESCRIPTION	DRAW.	DATE.



Recommended P.C.B Layout
Layout Tolerance=+/-0.05mm

No. of Pins	Dimension		
	DIM.A	DIM.B	DIM.C
02	4.50	3.50	1.50
03	6.00	5.00	3.00
04	7.50	6.50	4.50
05	9.00	8.00	6.00
06	10.50	9.50	7.50
07	12.00	11.00	9.00
08	13.50	12.50	10.50
09	15.00	14.00	12.00
10	16.50	15.50	13.50
11	18.00	17.00	15.00
12	19.50	18.50	16.50
13	21.00	20.00	18.00
14	22.50	21.50	19.50
15	24.00	23.00	21.00
16	25.50	24.50	22.50

Material:

Insulator : NYLON 9T (UL94V-0)

Contact : Phosphor Bronze

Contact Plated : Gold over Nickel or Tin

Specification

Current Rating : 3A

Instant Current : 5A

Voltage Rating : 20V

Contact Resistance : 30mΩ

Insulation Resistance : 100MΩ

Dielectric Voltage : 500V

Operating Temperature : -25°~85°

AUGO

东莞市欧高电子有限公司

Dongguan Augo Electronics Co.,Ltd

地址:广东省东莞市黄江镇新市东江路8号富汇创园 电话:0769-83383791

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

REV:

01

SIZE:

A4

SCALE: 1:1

UNIT: mm

SHEET: 1/1



UNLESS OTHERWISE
SPECIFIED,TOLERANCE:

X.

±0.20

X.x

±0.15

X.xx

±0.10

ANGULAR

±2°

TITLE:

BATTERY MALE 1.5PITCH
BOARD TO BOARD CONNECTOR

PART NO:

AUGO-B15M-3P-30

DESIGN

G.C.CHEN

DATE

DRAWING

Y.C.ZHANG

DATE

CHECK

D.J.WANG

DATE

SCALE

1:1

PAGE

1 OF 1